# MAGEWELL

# **Ultra Stream HDMI Technical Specifications**

Copyright (c) 2011–2021 Magewell Electronics Co., Ltd. All rights reserved.

Specifications are based on current hardware, firmware and software revisions, and are subject to change without notice.

HDMI, the HDMI logo and High-Definition Multimedia interface are trademarks or registered trademarks of HDMI Licensing LLC.

Revised 27/11/2020

## **Input Features**

- Max HDMI input & loop-through signals:
  - 4096x2160 4:2:0 60fps
  - 4096x2160 4:4:4/4:2:2 30fps
- Supported HDMI inputs include:
  - 4096x2160p/3840x2160p 23.98/24/25/29.97/30/59.94/60
  - 2560x1080p 23.98/24/25/29.97/30/50/59.94/60
  - 1920x1080p 23.98/24/25/29.97/30/50/59.94/60/100/119.88/120
  - 1920x1080i 25/29.97/30/50/59.94/60
  - 1280x720p 23.98/24/25/29.97/30/50/59.94/60/144
  - 720x576p 50/100/144
  - 720x576i 25/50
  - 720x480p 59.94/60/144
  - 720x480i 29.97/30
- 8/10/12-bit color
- Input & loopthrough 8-Channel, 24-bit HDMI embedded audio, 192kHz sample rate
- Input audio from 3.5mm microphone
- HDMI Input and loop-through interfaces: HDMI 1.4a, DVI-D

# **Encoding Features**

- Dual stream encoding: main stream and sub stream
- Max bitrate:
  - Main Stream 8Mbps
    - Sub Stream 2Mbps
- Supported resolutions:
  - HD: 1920x1080, 1600x1200, 1600x900, 1440x1080, 1440x900, 1280x1024, 1280x960, 1280x800, 1280x720, 1024x768
  - SD: 960x540, 800x600, 768x576, 720x576, 720x540, 640x480, 640x360, 480x360, 480x270
- Supported frame rates: 60/59.94/50/30/29.97/25/24/15/10/5fps
- H.264/H.265(HEVC) video encoders
- Encoding 2-channel AAC at 48kHz, 16-bit
- Supported audio bitrates: 256/192/128/96/64/48/32/16 kbps
- Extracting audio from input signal and output through 3.5mm headphone

# **Streaming Features**

- Natively support streaming to Facebook, Twitch and YouTube
- Supported streaming protocols including RTSP/RTMP/RTMPS
- Up to 2 streaming sessions simultaneously

# **Recording Features**

- Recording to a USB flash drive, internal SD storage and paired mobile device simultaneously
- To a USB Flash Drive
  - support auto-recording, normal recording
  - recording as MP4 or MOV files
- To internal SD storage (32GB)
  - support auto-recording
  - support loop-styled or normal recording
  - recording as MP4 or MOV files

- To paired mobile device
  - recording as MP4 files
  - taking still image snapshots during recording
  - timer recording at 15s, 30s, 1min, 2min, 5min

## **Management & Configuration**

- Provide comprehensive information regarding the system information of device and working status in real-time
- Configure parameters of volume and color, color format and quantization of input and output signals, stream profiles, as well as the network connection
- Update firmware
- Remotely control via App or WebUI
- WebUI supports IE/Edge/Firefox/Chrome/Safari/Opera web browsers
- Provide HTTP APIs

#### Network

- Wired Ethernet network: 10/100/1000Mbps
- Wi-Fi 802.11 a/b/g/n/ac
- 3G/4G USB mobile broadband Modem (not included)
- Bluetooth 4.0 BLE

## **LED Indicators**

- Indicate the state of the input signal, Ethernet Network, Wi-Fi, USB flash drive
- Indicate the working state of the device: startup, recording, streaming, updating

## **Power Supply and Consumption**

- DC 5V/2A
- Max power consumption: ~9.6 W

### **Form Factor**

• 94.20mm x 94.20mm x 22.30mm

### Accessories

- AC adapter
- HDMI cable

# **Working Environment**

- Operating temperature: 0 to 40 deg C
- Storage temperature: -20 to 70 deg C
- Relative humidity: 5% to 90% non-condensing