



# HA5-Plus

Bring HDMI and 3G-SDI devices together for a full range of monitoring and recording solutions in the edit suite, on set or at live events. Convenient USB setup using AJA MiniConfig on Mac or PC for easy remote configuration.

**\$395 US MSRP**

<https://www.aja.com/products/ha5-plus>

## Video Formats

- (HD) 1920 x 1080p
- (HD) 1920 x 1080i
- (HD) 1280 x 720p
- (SD) 720 x 576p
- (SD) 720 x 576i
- (SD) 720 x 480p
- (SD) 720 x 480i

Note: HDCP content not supported

## Output Formats

- (HD) 1920 x 1080i 50, 59.94, 60
- (HD) 1920 x 1080p 23.98, 24, 25, 29.97, 30
- (HD) 1920 x 1080i 50, 59.94, 60
- (HD) 1080p 50, 59.94, 60 - SMPTE 425-1 Level A mapping structure 1 (1920 x 1080 4:2:2 10-bit YCbCr)
- (HD) 720p 50, 59.94, 60
- (SD) 625i 50
- (SD) 525i 59.94

## Video Input

- HDMI with embedded audio, up to 8-Channels

## Video Output

- 3G-SDI with embedded audio

## Audio Input

- 2-Channel RCA style analog audio (-10dBu nominal)

## Audio Output

- SDI embedded audio

## Size (w x d x h)

- 4.6" x 2.4" x 1.0" (116.84 x 60.96 x 25.4 mm)

## Power

- Uses AJA power supply model DWP-U-R1, included with purchase
- 100-240V, 50/60 Hz universal input
- +5V DC regulated, 7.5 watt capacity

## Environment

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)